

Olejobá hadice, T619 AA, TSH, 16bar/-0,8bar, -30°C/+70°C,
NBR/CR, řerná

↔		↔		⌚	⌒))		⚙	
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
19	3/4	31	1,22	16	240	95	3,75	100	0,690	0,460
25	1	37	1,46	16	240	150	6,00	100	0,840	0,560
32	1 1/4	44	1,73	16	240	175	7,00	100	1,030	0,690
38	1 1/2	51	2,01	16	240	225	9,00	100	1,180	0,790
50	2	66	2,60	16	240	275	11,00	100	1,760	1,180
51	2	67	2,64	16	240	275	11,00	100	1,790	1,200
63	2 1/2	79	3,11	16	240	300	12,00	90	2,330	1,570
75	3	91	3,58	16	240	350	14,00	90	2,790	1,880
76	3	92	3,62	16	240	350	14,00	90	2,820	1,900
100	4	116	4,57	16	240	450	17,50	90	3,760	2,530
102	4	118	4,65	16	240	450	17,50	90	3,820	2,570

NA	LA	NEU	EMEA	SA	AP	AU
----	----	-----	------	----	----	----



619AA

**Fuel-oil S&D 16 bar (240 psi)
EN 12115 - exceeds EN 1761 - TRBF 131/2**

Tube: Black conductive NBR

Reinforcement: High tensile textile cords with embedded steel helix wire - antistatic wire

Cover: Black conductive CR - abrasion, ozone, hydrocarbon and fire resistant

Use: Fuel and oil suction and delivery. Designed for long service life in heavy duty applications

Safety factor: 4:1

Temperature: -30 °C +70 °C (-22 °F +158 °F)